

STACOR AQUA ACRYL

Anti-corrosive top coat for steel structures and concrete.

1. Product description:

STACOR AQUA ACRYL is a premium-class acrylic emulsion paint for finishing coats on steel surfaces. It combines the functions of an anti-corrosion and a finishing coating. Applied to the surface, it provides corrosion protection of steel in combination with intumescent, primer and intermediate coats.

2. Range of use:

Intended for finishing and top coats on steel structures and as a decorative coating over intumescent fire-protection systems for indoor service and under canopies. It can also be used in residential, public and medical premises.

3. Material properties

Colour:	according to the RAL catalogue
Theoretical consumption:	0.15-0.20 kg/m ²
Gloss:	deep matt
Shelf life:	12 months from the date of manufacture.
Storage conditions:	In a cool and dry environment at temperature from +5 °C to +40 °C, in tightly sealed container, protecting from moisture and direct sunlight.
Packaging norm:	STACOR AQUA ACRYL: 20 kg (net)

4. Technical data

Preparation of material:	The material is supplied ready to use. Stir thoroughly prior to application. Stop stirring when a homogeneous mixture is obtained.
Application temperature:	Min 0 °C max +50 °C
Relative humidity:	30...80 % during application. During application and drying the surface temperature should be +3 °C higher than the dew point temperature.
Application method:	By brush, spray or roller.
Thinner:	Water
Drying time:	the next coat can be applied after 2 hours.

